

# AFL3-W07A-AL2

Intel® Celeron N3350 (2M Cache, up to 2.4 GHz)  
TDP 6W



## Features

- » W7" light industrial interactive panel PC
- » 12V DC input with lockable DC jack
- » Selectable AT/ATX power mode
- » Built-in speakers
- » On board IEEE802.3 at standard
- » IP65 compliant front panel
- » Touch screen with anti-UV / anti-glare coating
- » HDMI output
- » RS232/422/485 DB9 connector

## Specifications

<b>System</b>	
Cooling method / System Fan	Fanless
CPU	Intel® Celeron N3350 (2M Cache, up to 2.4 GHz) TDP 6W
Storage	1 x M.2 B+M key PCIe 2242 (USB/SATA signal)
<b>Communication</b>	
Bluetooth	Bluetooth V4.1
Wireless	IEEE 802.11a/b/g/n/ac
<b>I/O Interface</b>	
Ethernet	2x PCIe GbE by Intel® i211 controller
Audio	AMP 2W (internal speaker)
Audio Codec	ALC269
RAM	one 204-pin 1866MHz DDR3L DIMMs support up to 8GB
<b>Power</b>	
Power Requirement	12V , 3A
<b>Environment</b>	
Operating Temperature	-20°C ~ 50°C
Humidity	10% to 95% (non-condensing)
Storage Temperature	-20°C~60°C
<b>Weight</b>	
Weight	0.73kg/1.81kg
<b>LCD</b>	
Size	7"
Resolution	1024 x 600 (16:9)
Brightness (cd/m2)	500
Contrast Ratio	700:1
LCD Color	16.7M
Pixel Pitch (mm)	0.1506 (H) x 0.1432 (V)
Viewing Angle (H-V)	150° / 145°
Backlight MTBF	20000 (LED backlight)
<b>Touch</b>	
Touch Screen	Projected capacitive type with USB interface (anti-UV)
Touch Controller	EXC80H60
<b>I/O Interface</b>	

I/O Interface	1 x AT/ATX Switch
	1 x Clear CMOS
	1 x RS-232 (RS232/422/485 (by DB9))
	1 x HDMI
	1 x LAN (GbE)
	1 x Power Switch
	2 x USB 3.2 Gen1x1 (5Gb/s)
	1 x Reset Button
	1 x Power In
OS Support	
OS Support	Microsoft Windows 10 / Windows 11, Linux

## Ordering Information

AFL3-W07A-AL2-N1/P/PC/4G-R10	7" 500cd/m2 1024x600 fanless Panel PC with Intel® Celeron® Processor N3350 (6W) on-board Processor , w/COM , on-board POE at, 1*4GB DDR3L , WiFi module, PCAP touch,R10
------------------------------	---

## Packing List

4 x Round head machine screw	4 x Pan head machine screw
1 x Power cord	1 x Power adapter