


PUZZLE-M902

軟體定義路由器



Features

- » 搭載 Marvell® CN9130 四核心 Armv8 Cortex-A72 2200 MHz 高性能的處理器
- » 6 埠 2.5 GbE 的 RJ-45 網路埠
- » 3 埠 10 GbE 的 RJ-45 網路埠
- » 內存 4 GB eMMC , 1 x Console (預留 pin header), 1 x 重置按鈕
- » LED 燈號顯示：機器狀態顯示燈號/
電源狀態顯示燈號以及 WAN/LAN 顯示燈號

Specifications

| | |
|-----------------------------|---|
| Form Factor | |
| Form Factor | Desktop |
| System | |
| CPU | Marvell® CN9130 quad-core Armv8 Cortex-A72 @ up to 2200 MHz |
| Cooling method / System Fan | 1 system fan |
| Physical Characteristics | |
| Dimensions (LxWxH) (mm) | 226 x140 x 50.5 |
| Storage | |
| Storage | 1 x eMMC: onboard 4 GB |
| | 1 x M.2(NGFF): 2242/2280 M Key M.2 PCIe Gen. 3 x1 |
| I/O Interface | |
| Ethernet | 3 x Fiber: 10 GbE |
| | 6 x LAN: 2.5 GbE |
| I/O Interface | 1 x External USB 3.2 Gen1x1 |
| Environment | |
| Operating Temperature | 0°C ~ 40°C (32°F ~ 104°F) |
| Storage Temperature | -20°C ~ 75°C (-4°F ~ 167°F) |
| Humidity | 5~95% non-condensing, wet bulb: 27 °C |
| Certifications | |
| Safety & EMC | CE/FCC/BSMI (BSMI safety)/VCCI, LVD |
| OS Support | |
| OS Support | OpenWrt |

Ordering Information

| | |
|---------------------|--|
| PUZZLE-M902-CN1-R10 | Desktop Network Appliance with Marvell CN9130 Processor ,6 x 2.5GbE and 3 x10 GbE on Board 4GB eMMC & 1x M.2 slot, RoHS. |
|---------------------|--|

Packing List

| | |
|----------------|-------------------|
| 1 x Power cord | 1 x Power adapter |
|----------------|-------------------|

Why You Need Software Defined Router?

High Reliability, Performance and Availability



HIGH SCALABILITY
Rich open resource services to achieve any requirement



SUPER SPEED
Design with 2.5GbE and 10GbE ports for faster package transfer



FASTER TIME TO MARKET
Deploy network applications and services faster by leveraging open software packages

Get Your Office Ready for New Gen. Software Defined Router

The growing number of connected personal and IoT devices has led to an overall increase in network density. The PUZZLE-M902 is IEI's latest product series – Software Defined Router, which is pre-installed with OpenWrt and features high speed and high flexibility to optimize your network performance. This series is integrated with 2.5GbE and 10GbE ports and the interfaces can be defined with various combination to meet your demands. Moreover, its function can also be expanded by open source applications supported in the OpenWrt community. It is ideally suited for a wide range of applications, such as SOHO and SMB networking infrastructure.



High-end Arm-based Platform with Marvell Quad-core SoC

The Marvell CN9130 is a quad-core Armv8 Cortex-A72 system-on-chip (SoC). The high-performance processor offers a complete function and acceleration for networking and security applications. It can accelerate the packet processing for NAT, QoS and packet filtering, and offload the processor on multiple IPSec/SSL VPN tunneling.




High computing with quad-core SoC



Accelerate NAT, QoS, packet filtering, and offload IPSec/SSL VPN tunneling

Flexible High-speed Network Deployment

The Marvell CN9130 is a quad-core Armv8 Cortex-A72 system-on-chip (SoC). The high-performance processor offers a complete function and acceleration for networking and security applications. It can accelerate the packet processing for NAT, QoS and packet filtering, and offload the processor on multiple IPSec/SSL VPN tunneling.



Built stability for multi-device connections

6 x 2.5 GbE 3 x 10 GbE

Super speed for package transfer

Customize Your Network with OpenWrt

The hottest open source project, OpenWrt, which is based on Linux-based embedded operating system and used on embedded devices to route network traffic. It uses the command line interface (ash shell) or the web interface (LuCI) to configure OpenWrt. Approximately 3,500 optional software packages can be installed through the opkg package management system. It provides detailed possibilities to configure common network-related functions, such as IPv4, IPv6, DNS, DHCP, VPN, shadowsocks, DLNA, routing, Dynamic DNS, firewall, NAT, port forwarding, file sharing via SAMBA, NFS, FTP, SFTP and MQ Telemetry Transport through Mosquitto.




The hottest open source project for router

3,500

Various software packages you can have



Simple and Visible Network Operation

Powered by OpenWrt, the PUZZLE-M902 provides a user-friendly web interface, a clear dashboard and port indicators to help you handle daily network management tasks. Users can not only efficiently manage all connected wires through OpenWrt OS in real time, but also configure firewall, VPN, security and advanced network functions.



Make Security Configuration Easier than Ever

There are multiple packages available in the OpenWrt package repository and designed with clear user interface to support IT developer for installing and deploying the security function of network. OpenVPN, a virtual private network (VPN), and Firewall3 (fw3) which uses netfilter/iptables rule builder for firewall applications, are two of the most popular packages for creating high reliable network security.



Connection Configuration

Dimensions (Unit: mm)

