


# KINO-DH420

Mini-ITX SBC supports LGA1200 Intel® 10th Generation Core™ i9/i7/i5/i3/ Pentium®/Celeron® processor, DDR4, dual independent displays, triple 2.5 GbE LAN, M.2, SATA 6Gb/s, HD Audio and RoHS



## Features

1. LGA1200 Intel® 10th Generation Core™ i9/i7/i5/i3, Celeron® and Pentium® processor
2. Support triple Intel® 2.5Gb Ethernet controller
3. Support HDMI, DP display output
4. Support 1 x PCIe Gen3 x16, 1 x M.2 A key, 1 x M.2 B key expansion

## Specifications

Form Factor	
Form Factor	Mini-ITX Motherboard
System	
CPU	LGA1200 Intel® 10th Generation Core™ i9/i7/i5/i3, Celeron® and Pentium® processor
Chipset	Intel® H420E
Memory	Two 260-pin 2933 MHz Dual-Channel DDR4 SO-DIMMs supported up to 64GB
Memory Max.	up to 64GB
Cooling method / System Fan	1 x CPU fan connector (1x4 pin) 2 x System fan connector (1x4 pin)
Physical Characteristics	
Dimensions (LxWxH) (mm)	170mm x 170mm
Net Weight	400g
Storage	
Storage	2 x SATA : 6Gb/s (no RAID) 1 x M.2(NGFF) : B key (support NVME storage)
I/O Interface	
Display Output	1 x HDMI up to 4096 x 2160 @30Hz 1 x Display Port up to 4096 x 2304 @60Hz
Ethernet	3 x LAN - LAN1: Intel® i225LM GbE controller (colay i225v) LAN2: Intel® i225v GbE controller (colay i225LM) LAN3: Intel® i225v GbE controller (colay i225LM)
Audio	1 x Line out 1 x Mic 1 x Front Audio : 2x5 pin 1 x HD Audio : Realtek ALC888S HD codec
I/O Interface	2 x External RS-232 1 x Internal RS-232 : 2x5 pin, P=2.00

	1 x Internal RS-422/485 : RS-485 support AFC
	2 x External USB 2.0 : Type-A
	4 x External USB 3.2 Gen1x1 : 5Gb/s(Type-A)
	2 x Internal USB 2.0 : 2x4 pin, P=2.00
	1 x DIO : 8-bit digital I/O (2x5 pin)
Expansion	1 x PCIe x16
	2 x M.2(NGFF) - 1 x M.2 A key (2230) (PCIe Gen 3 x1/USB 2.0) 1 x M.2 B key (3042/3052/2242/2280) w/ SIM holder (PCIe Gen 3 x2/USB 2.0)
<b>Other Features</b>	
TPM	Intel® PTT(TPM 2.0)
<b>Power</b>	
Power Consumption	12V@12.408A (Intel® Core™ i7-10900E CPU with two 32 GB 2933 MHz DDR4 memory, EuP/ErP mode disabled)
Power Supply	DC 12V input
	1 x ATX power connector (2x4 pin)
	1 x DIN 4-pin DC Jack
	Support AT/ATX mode
	ErP/EuP Compliant
<b>Environment</b>	
Operating Temperature	0°C – 60°C
Storage Temperature	-30°C – 70°C
Humidity	5% ~ 95%, non-condensing
<b>Certifications</b>	
Safety & EMC	CE/FCC compliant

## Ordering Information

KINO-DH420-R10	Mini-ITX SBC supports LGA1200 Intel® 10th Generation Core™ i9/i7/i5/i3, Celeron® and Pentium® processor, DDR4, dual independent displays, triple 2.5GbE LAN, M.2, SATA 6Gb/s, HD Audio and RoHS
----------------	---

## Packing List

1 x KINO-DH420 single board computer	1 x SATA cable
1 x I/O shielding	1 x QIG